

View Online at <https://aerobasegroup.com/nsn/5935-00-927-6746>

Thread Class:

2a and 2b

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, internal coupling

Overall Length:

1.038 inches

Overall Width:

0.525 inches

Threaded Device Type:

Coupling facility and coupling facility

Mating End Quantity:

2

Contact Position Arrangement Style:

Sma 2nd mating end

Contact Removability:

Removable all mating ends single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell and internally threaded shell

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends single contact grouping

Thready Qty Per Inch (tpi):

28 and 36

Thread Size:

0.438 inches and 0.250 inches

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response all mating ends single contact grouping

Shell Material:

Steel

Shell Surface Treatment:

Passivate

Included Contact Quantity:

1 2nd mating end single contact grouping

Included Contact Type:

Coaxial socket 1st mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.002 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef and unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.