## NSN 5935-00-928-1107

Electrical Receptacle Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-00-928-1107



**Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Right angle type **Overall Length:** 2.100 inches **Overall Height:** 0.610 inches **Overall Width:** 0.360 inches **Distance Between Mounting Facility Centers:** 1.800 inches **Threaded Device Type:** Mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Guide pin/socket Thready Qty Per Inch (tpi): 40 Thread Size: 0.112 inches **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Solder well single mating end single contact grouping **Insert Material Specification:** 

Mil-p-19833, type gdi-30f military specification single material response single mating end

# NSN 5935-00-928-1107

Electrical Receptacle Connector - Page 2 of 2



### **Included Contact Quantity:**

15 single mating end single contact grouping

### **Included Contact Type:**

Round pin single mating end single contact grouping

### **Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

### **Precious Material And Weight:**

0.015 gold grains, troy and 0.015 silver grains, troy

**Precious Material:** 

Gold and silver

**Thread Series Designator:** 

Unc

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-p-19833 spec.