

View Online at https://aerobasegroup.com/nsn/5935-00-928-1181

| Thread Class | |
|--|--|
| Thread Class: | |
| 2a Thread Direction | |
| Thread Direction: | |
| Right-hand | |
| Body Style: | |
| Straight shape, flush mount | |
| Overall Length: | |
| Between 1.099 inches and 1.119 inches | |
| Overall Height: | |
| Between 3.927 inches and 3.947 inches Overall Width: | |
| | |
| Between 3.365 inches and 3.385 inches | |
| Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.995 inches and 1.005 inches | |
| | |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 2.870 inches and 2.880 inches | |
| Distance From Mounting Shoulder To Front Face: | |
| Between 0.052 inches and 0.072 inches | |
| Threaded Device Type: | |
| Coupling facility | |
| Mating End Quantity: | |
| 2 | |
| Contact Position Arrangement Style: | |
| 78 single mating end | |
| Polarization Method: | |
| 1 polarization post | |
| Shell Type: | |
| Solid | |
| Connector Locking Method: | |
| Screw | |
| Thready Qty Per Inch (tpi): | |
| 12 | |
| Thread Size: | |
| 0.312 inches | |
| Insert Material: | |
| Plastic diallyl phthalate all mating ends | |
| Shell Material: | |
| Aluminum alloy | |
| Shell Surface Treatment: | |
| Cadmium | |
| Special Features: | |
| Mtd by 0.144 in. Diameter mtg holes and polarized at position y | |
| | |



Thread Series Designator:

Uns

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0