Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-928-1322

#### **Body Style:**

Straight shape, flange mount, external coupling

- **Overall Length:**
- 1.656 inches
- **Overall Height:**
- 1.562 inches
- **Overall Width:**
- 1.562 inches
- **Unthreaded Mounting Hole Diameter:**
- 0.120 inches
- Center To Center Distance Between Mounting Facilities Parallel To Height:

#### 1.250 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

- 1.250 inches
- **Distance From Mounting Shoulder To Front Face:**
- 0.556 inches
- Mating End Quantity:
- 1
- **Contact Position Arrangement Style:**
- 22-32 single mating end
- **Contact Removability:**
- Removable single mating end single contact grouping
- Contact Maximum Current Rating In Amps:
- 7.5 single mating end single contact grouping
- Contact Maximum Ac Voltage Rating In Volts:
- 500.0 single mating end single contact grouping
- Contact Maximum Dc Voltage Rating In Volts:
- 700.0 single mating end single contact grouping
- **Polarization Method:**
- Key, multiple key groove
- **Insert Position In Deg:**
- 0.0
- Shell Type:
- Potting
- **Connector Locking Method:**
- Bayonet pin
- **Connector Cable Strain Relief Method:**
- Potting type
- **Terminal Location:**
- Back single mating end single contact grouping
- **Contact Material:**
- Copper alloy single mating end single contact grouping

Electrical Receptacle Connector - Page 2 of 2



# **Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

### Insert Material:

Rubber single mating end

# Terminal Type:

Solder well single mating end single contact grouping

# Shell Material:

Aluminum alloy

# Shell Surface Treatment:

Chromate

# Included Contact Quantity:

32 single mating end single contact grouping

# Bushing Accommodation Hole Shape:

Round

### Included Contact Type:

Round socket single mating end single contact grouping

#### **Special Features:**

Translucent nylon boot held in place by a threadedring

#### **Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

### **Precious Material And Weight:**

 $0.032 \ \text{gold grains}, \ \text{troy} \ \text{and} \ 0.032 \ \text{silver grains}, \ \text{troy}$ 

# Precious Material:

Gold and silver

# Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

#### Fiig:

A039b0