NSN 5935-00-928-1970

Electrical Plug Connector Body - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5935-00-928-1970 |
|---|
| Thread Class: |
| 2a and 2b |
| Thread Direction: |
| Right-hand and right-hand |
| Body Style: |
| Hood, top opening w/clamp |
| Overall Length: |
| 2.786 inches |
| Overall Height: |
| 2.625 inches |
| Overall Width: |
| 0.875 inches |
| Cable Entrance Diameter: |
| 0.875 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 50 single mating end |
| Polarization Method: |
| Jackscrew |
| Shell Type: |
| Hood, top opening |
| Connector Locking Method: |
| Jackscrew-socket |
| Connector Cable Strain Relief Method: |
| Cable clamp |
| Thread Size: |
| 0.138 inches and 0.138 inches |
| Insert Material: |
| Plastic diallyl phthalate single mating end |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Cadmium |
| |

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

Shell Material Specification:

Qq-a-250/8 federal specification single material response

Insert Material Specification:

Mil-m-19833, ty gdi-30 military specification single material response single mating end

NSN 5935-00-928-1970

Electrical Plug Connector Body - Page 2 of 2



| Special Features: |
|---|
| Elongated cable clamp 0.875 in. Lg by 0.750 in. $\ensuremath{\mathrm{W}}$ |
| Thread Series Designator: |
| Unc and unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |

Mil-std (military Standard):

Mil-m-19833 spec.