

View Online at <https://aerobasegroup.com/nsn/5935-00-928-4293>

**Body Style:**

Hood, top opening w/clamp

**Overall Length:**

2.120 inches

**Overall Height:**

2.480 inches

**Overall Width:**

0.880 inches

**Cable Entrance Diameter:**

0.550 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

34 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

7.5 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

4100.0 single mating end single contact grouping

**Polarization Method:**

Jackscrew

**Shell Type:**

Hood, top opening

**Connector Locking Method:**

Jackscrew-socket

**Connector Cable Strain Relief Method:**

Integral clamp

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, cl 1 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Crimp single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium

**Shell Surface Treatment Specification:**

Qq-p-416, type 1, class 1 federal specification single treatment response

**Shell Material Specification:**

Qq-a-591, alloy a13 federal specification single material response

**Included Contact Quantity:**

34 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.