## NSN 5935-00-928-4304



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-928-4304 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Rectangular shape **Overall Length:** 3.000 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 2.375 inches **Overall Height:** 1.140 inches **Overall Width:** 1.740 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.875 inches **Threaded Device Type:** Mounting stud **Mating End Quantity: Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Guide pin/socket Shell Type: Solid **Connector Locking Method:** Friction Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.138 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping

Insert Material:

Plastic polycarbonate single mating end

**Terminal Type:** 

Crimp single mating end single contact grouping

## NSN 5935-00-928-4304

Electrical Receptacle Connector - Page 2 of 2



Ohadi Markariak
Shell Material:
Aluminum
Shell Surface Treatment:
Anodize
Unable To Decode:
Unable to decode and unable to decode and unable to decode and unable to decode
Included Contact Quantity:
132 single mating end single contact grouping
Included Contact Type:
Flat socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.132 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0