Electrical Receptacle Connector - Page 1 of 2

AeroBase

View Online at https://aerobasegroup.com/nsn/5935-00-928-7850

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
0.594 inches
Overall Diameter:
0.145 inches
Distance From Mounting Shoulder To Front Face:
0.426 inches
Threaded Device Type:
Mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
Nonstd single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
1.5 single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Friction
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
Thready Qty Per Inch (tpi):
32
Thread Size:
0.190 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy 360 single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Insert Material:
Plastic fluorocarbon single mating end
Contact Surface Treatment Specification:
Mil-g-45204 type 1, grade c, cl 2 military specification 1st treatment response single mating end single

Mil-g-45204 type 1, grade c, cl 2 military specification 1st treatment response single mating end single contact grouping and mil-c-14550, cl

4 military specification 2nd treatment response single mating end single contact grouping



Terminal Ty	De:
Solder well s	ngle mating end single contact grouping
Contact Mat	erial Specification:
Qq-b-626 fec	eral specification single material response single mating end single contact grouping
Shell Materia	al:
Copper alloy	360
Shell Surfac	e Treatment:
Gold	
Shell Materia	al Specification:
Qq-b-626 fec	eral specification single material response
Included Co	ntact Quantity:
1 single mati	ng end single contact grouping
Bushing Ace	commodation Hole Shape:
Round	
Included Co	ntact Type:
Coaxial pin s	ingle mating end single contact grouping
Precious Ma	terial And Location:
Contact and	shell surfaces gold
Precious Ma	terial And Weight:
0.105 gold gr	ains, troy
Precious Ma	terial:
Gold	
Thread Serie	es Designator:
Unf	
Shelf Life:	
N/a	
Unit Of Meas	sure:
Demilitarizat	ion:
No	
Fiig:	
A039b0	
Mil-std (milit	ary Standard):
Mil-g-45204 s	spec.