

View Online at <https://aerobasegroup.com/nsn/5935-00-928-8173>

**Thread Class:**

2a and 2b

**Thread Direction:**

Right-hand

**Body Style:**

Hood, top opening w/clamp

**Overall Length:**

1.250 inches

**Overall Height:**

1.430 inches

**Overall Width:**

0.440 inches

**Environmental Protection:**

Shock resistant and vibration resistant

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

34 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Polarization Method:**

Jackscrew

**Shell Type:**

Hood, top opening

**Connector Locking Method:**

Jackscrew-socket

**Connector Cable Strain Relief Method:**

Cable clamp

**Cable Opening Length:**

0.510 inches

**Cable Opening Width:**

0.260 inches

**Thready Qty Per Inch (tpi):**

56

**Thread Size:**

0.086 inches

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate glass filled single mating end

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Aluminum

**Shell Surface Treatment:**

Anodize

**Included Contact Quantity:**

34 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.034 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0