NSN 5935-00-929-0331

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-929-0331 **Overall Length:** 1.031 inches **Overall Height:** 1.094 inches Overall Width: 1.094 inches **Environmental Protection:** Moisture resistant and salt water resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.120 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 0.812 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.812 inches **Mating End Quantity: Contact Position Arrangement Style:** 12-p all mating ends **Contact Removability:** Nonremovable all mating ends single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 all mating ends single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 all mating ends single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 all mating ends single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: **Connector Locking Method:** Detent **Contact Material:** Copper alloy all mating ends single contact grouping **Contact Surface Treatment:** Gold all mating ends single contact grouping **Insert Material:** Glass all mating ends

Shell Material: Aluminum alloy

NSN 5935-00-929-0331

Electrical Receptacle Connector - Page 2 of 2



0
Shell Surface Treatment:
Tin and cadmium
Included Contact Type:
Round socket 2nd mating end single contact grouping
Special Features:
Hermetic seal
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.024 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039h0