

View Online at <https://aerobasegroup.com/nsn/5935-00-929-4438>

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.656 inches

Overall Diameter:

0.812 inches

Environmental Protection:

Shock proof and vibration proof

Cable Entrance Diameter:

0.100 inches

Distance From Mounting Shoulder To Front Face:

0.937 inches

Mounting Facility Thickness:

0.312 inches

Threaded Device Type:

Coupling facility and mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

N single mating end

Contact Removability:

Removable single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Connector Cable Strain Relief Method:

Compression nut

Thready Qty Per Inch (tpi):

24 and 24

Thread Size:

0.625 inches and 0.625 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204 type 2, cl 2 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Copper alloy

Included Contact Quantity:

1 single mating end single contact grouping

Bushing Accommodation Hole Shape:

Round w/double flat

Included Contact Type:

Coaxial socket single mating end single contact grouping

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef and unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.