Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-929-6123

Body Style: Straight shape Overall Length: 1.556 inches Overall Width: 0.509 inches Unthreaded Mounting Hole Diameter: Between 0.115 inches and 0.125 inches Distance Between Mounting Facility Centers: 1.317 inches Mating End Quantity: 1 Contact Position Arrangement Style: 40c67 single mating end Centact Removability: Removable single mating end single contact grouping
Overall Length:1.556 inchesOverall Width:0.509 inchesUnthreaded Mounting Hole Diameter:Between 0.115 inches and 0.125 inchesDistance Between Mounting Facility Centers:1.317 inchesMating End Quantity:1Contact Position Arrangement Style:40c67 single mating endContact Removability:
1.556 inches Overall Width: 0.509 inches Unthreaded Mounting Hole Diameter: Between 0.115 inches and 0.125 inches Distance Between Mounting Facility Centers: 1.317 inches Mating End Quantity: 1 Contact Position Arrangement Style: 40c67 single mating end Contact Removability:
Overall Width:0.509 inchesUnthreaded Mounting Hole Diameter:Between 0.115 inches and 0.125 inchesDistance Between Mounting Facility Centers:1.317 inchesMating End Quantity:1Contact Position Arrangement Style:40c67 single mating endContact Removability:
0.509 inches Unthreaded Mounting Hole Diameter: Between 0.115 inches and 0.125 inches Distance Between Mounting Facility Centers: 1.317 inches Mating End Quantity: 1 Contact Position Arrangement Style: 40c67 single mating end Contact Removability:
Unthreaded Mounting Hole Diameter: Between 0.115 inches and 0.125 inches Distance Between Mounting Facility Centers: 1.317 inches Mating End Quantity: 1 Contact Position Arrangement Style: 40c67 single mating end Contact Removability:
Between 0.115 inches and 0.125 inches Distance Between Mounting Facility Centers: 1.317 inches Mating End Quantity: 1 Contact Position Arrangement Style: 40c67 single mating end Contact Removability:
Distance Between Mounting Facility Centers: 1.317 inches Mating End Quantity: 1 Contact Position Arrangement Style: 40c67 single mating end Contact Removability:
1.317 inches Mating End Quantity: 1 Contact Position Arrangement Style: 40c67 single mating end Contact Removability:
Mating End Quantity: 1 Contact Position Arrangement Style: 40c67 single mating end Contact Removability:
1 Contact Position Arrangement Style: 40c67 single mating end Contact Removability:
Contact Position Arrangement Style: 40c67 single mating end Contact Removability:
40c67 single mating end Contact Removability:
Contact Removability:
Polarization Method:
Mating end
Shell Type:
Solid
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Steel
Shell Surface Treatment:
Cadmium
Insert Material Specification:
Mil-m-19833, type gdi-30f military specification single material response single mating end
Included Contact Quantity:
10 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.010 gold grains, troy and 0.010 silver grains, troy

Electrical Receptacle Connector - Page 2 of 2



Precious Material:

Gold and silver

Test Data Document:

56232-1211424 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

56232-1211424 manufacturers specification control

Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig: A039b0 Mil-std (military Standard): Mil-m-19833 spec.