Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-929-7626

#### **Body Style:**

Straight edge type w/card guide

### **Overall Length:**

3.145 inches

# **Overall Height:**

1.148 inches

### **Overall Width:**

0.578 inches

#### **Unthreaded Mounting Hole Diameter:**

0.128 inches

### **Distance Between Mounting Facility Centers:**

2.875 inches

#### **Board Accommodated Length:**

### 2.615 inches single board

### **Board Accommodated Width:**

0.074 inches

### Mating End Quantity:

1

## Contact Removability:

Nonremovable single mating end single contact grouping

### **Contact Maximum Current Rating In Amps:**

10.0 single mating end single contact grouping

## Polarization Method:

Guide pin/socket

### **Terminal Location:**

Back single mating end single contact grouping

### **Contact Material:**

Copper alloy single mating end single contact grouping

### Contact Surface Treatment:

Gold single mating end single contact grouping and copper single mating end single contact grouping

### **Insert Material:**

Plastic diallyl phthalate single mating end

### **Terminal Type:**

Solder well single mating end single contact grouping

### **Insert Material Specification:**

Mil-m-14, type sdg-f military specification single material response single mating end

## **Included Contact Quantity:**

24 single mating end single contact grouping

### Included Contact Type:

Hermaphrodite single mating end single contact grouping

# **Precious Material And Location:**

Contact surfaces gold



**Precious Material And Weight:** 

0.024 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.