# NSN 5935-00-929-9968

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-929-9968

**Body Style:** 

Straight shape, internal coupling

**Overall Length:** 

0.965 inches

**Overall Diameter:** 

0.445 inches

**Environmental Protection:** 

Moisture resistant and vibration resistant and salt water resistant

**Cable Entrance Diameter:** 

Between 0.096 inches and 0.110 inches

**Mating End Quantity:** 

4

**Contact Position Arrangement Style:** 

Nonstd single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Frequency Rating:** 

1000.0 megahertz single mating end single contact grouping

**Polarization Method:** 

Keyway or multiple keyway

**Insert Position In Deg:** 

90.0 and 180.0 and 270.0

Shell Type:

Solid

**Connector Locking Method:** 

Bayonet latch

**Connector Cable Strain Relief Method:** 

Compression nut

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Contact Surface Treatment Specification:** 

Mil-g-45204, type 2, class 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, class 2, type 7 federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:** 

Solder well single mating end single contact grouping

**Shell Material:** 

Copper alloy

**Shell Surface Treatment:** 

Nickel

# NSN 5935-00-929-9968

Electrical Plug Connector - Page 2 of 2



#### **Shell Material Specification:**

Qq-b-626, composition 360 federal specification single material response

### **Insert Material Specification:**

Ams3651 federal specification single material response single mating end

### **Included Contact Quantity:**

1 single mating end single contact grouping

### **Included Contact Type:**

Coaxial pin single mating end single contact grouping

### **Precious Material And Location:**

Contact surface and shell surface gold

#### **Precious Material And Weight:**

0.105 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0

## Mil-std (military Standard):

Mil-g-45204 spec.