NSN 5935-00-930-2667



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-930-2667 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** Between 1.547 inches and 1.579 inches **Overall Diameter:** 0.595 inches **Environmental Protection:** Salt water resistant **Distance From Mounting Shoulder To Front Face:** Between 0.420 inches and 0.430 inches **Mounting Facility Thickness:** 0.156 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** Bnc single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.437 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping

Contact Surface Treatment: Silver single mating end single contact grouping

Insert Material:

Plastic tetrafluoroethylene single mating end

NSN 5935-00-930-2667

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Turret single mating end single contact grouping
Shell Material:
Copper alloy
Shell Surface Treatment:
Silver
Included Contact Quantity:
1 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round w/flat
Included Contact Type:
Coaxial socket single mating end single contact grouping
Precious Material And Location:
Contact @and shell surfaces silver
Precious Material And Weight:
0.001 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0