Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-930-3792

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.069 inches
Overall Diameter:
1.828 inches
Distance From Mounting Shoulder To Front Face:
0.807 inches
Mounting Facility Thickness:
Between 0.062 inches and 0.250 inches
Threaded Device Type:
Back shell and mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
20-39 single mating end
Contact Removability:
Nonremovable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
7.5 single mating end 2nd contact grouping
Contact Maximum Ac Voltage Rating In Volts:
500.0 single mating end all contact groupings
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end all contact groupings
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Thready Qty Per Inch (tpi):
18
Thread Size:
1.250 inches and 1.375 inches
Terminal Location:
Back single mating end all contact groupings

Electrical Receptacle Connector - Page 2 of 2



**Contact Material:** Copper alloy single mating end all contact groupings **Contact Surface Treatment:** Gold single mating end all contact groupings and silver single mating end all contact groupings **Insert Material:** Rubber single mating end **Terminal Type:** Solder well single mating end all contact groupings Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium **Shell Surface Treatment Specification:** Qq-p-416 federal specification single treatment response **Included Contact Quantity:** 37 single mating end 2nd contact grouping **Bushing Accommodation Hole Shape:** Round **Included Contact Type:** Round pin single mating end all contact groupings **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.039 gold grains, troy and 0.039 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0