NSN 5935-00-930-6146

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-930-6146 **Body Style:** Straight shape w/flange **Overall Height:** 1.438 inches **Overall Width:** 1.438 inches **Environmental Protection:** Corrosion resistant and moisture resistant and vibration resistant and shock resistant **Unthreaded Mounting Hole Diameter:** 0.094 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.188 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.188 inches **Distance From Mounting Shoulder To Front Face:** 0.500 inches **Mating End Quantity:** 2 **Contact Position Arrangement Style:** 37-2p all mating ends **Contact Removability:** Nonremovable all mating ends single contact grouping **Polarization Method:** Keyway or multiple keyway and keyway or multiple keyway **Insert Position In Deg:** 0.0 and 0.0 Shell Type: Solid **Connector Locking Method:** Spring friction **Contact Material:** Copper alloy all mating ends single contact grouping **Contact Surface Treatment:** Gold all mating ends single contact grouping **Insert Material:** Rubber all mating ends **Contact Surface Treatment Specification:** Mil-g-45204 military specification single treatment response all mating ends single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:**

Silver

NSN 5935-00-930-6146

Connector Adapter - Page 2 of 2



Shell Surface Treatment Specification:

Qq-s-365 federal specification single treatment response

Included Contact Quantity:

24 2nd mating end single contact grouping

Included Contact Type:

Round socket 2nd mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and shell surface silver

Precious Material And Weight:

0.048 gold grains, troy and 0.100 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.