NSN 5935-00-930-8890



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-930-8890 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Right angle type **Overall Length:** 2.900 inches **Overall Width:** 0.510 inches **Body Height:** 0.360 inches **Environmental Protection:** Corrosion resistant and humidity resistant and shock resistant and vibration resistant **Distance Between Mounting Facility Centers:** 2.600 inches **Threaded Device Type:** Mounting stud **Mating End Quantity: Contact Position Arrangement Style:** 23 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Contact **Connector Locking Method:** Friction Thready Qty Per Inch (tpi): **Thread Size:** 0.112 inches **Terminal Location:** Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

NSN 5935-00-930-8890

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Solder stud single mating end single contact grouping
Insert Material Specification:
Mil-m-16794 military specification single material response single mating end
Included Contact Quantity:
23 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.023 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0

Mil-std (military Standard):

Mil-m-16794 spec.