

View Online at https://aerobasegroup.com/nsn/5935-00-931-1829

Body Material: Plastic Thread Class: 2b Thread Direction: Right-hand Body Style: Top mount w/metal saddle and bushings Overall Length: 1.570 inches Overall Height: 0.716 inches Overall Width: 0.730 inches Mounting Hole Diameter: 0.138 inches Distance Between Mounting Facility Centers: Between 1.177 inches and 1.197 inches Mounting Hole Style: Two mounting holes/slots, in-line Contact Maximum Current Rating In Amps: 15.0 Contact Surface Treatment: Tin Accommodated Contact Quantity: 2 Polarization Type: Off center hole Projection Length Above Mounting Surface:
Thread Class: 2b Thread Direction: Right-hand Body Style: Top mount w/metal saddle and bushings Overall Length: 1.570 inches Overall Height: 0.716 inches Overall Width: 0.730 inches Mounting Hole Diameter: 0.138 inches Distance Between Mounting Facility Centers: Between 1.177 inches and 1.197 inches Mounting Hole Style: Two mounting holes/slots, in-line Contact Maximum Current Rating In Amps: 15.0 Contact Material: Beryllium copper Contact Surface Treatment: Tin Accommodated Contact Quantity: 2 Polarization Type: Off center hole Projection Length Above Mounting Surface:
2b Thread Direction: Right-hand Body Style: Top mount w/metal saddle and bushings Overall Length: 1.570 inches Overall Height: 0.716 inches Overall Width: 0.730 inches Mounting Hole Diameter: 0.138 inches Distance Between Mounting Facility Centers: Between 1.177 inches and 1.197 inches Mounting Hole Style: Two mounting holes/slots, in-line Contact Maximum Current Rating In Amps: 15.0 Contact Material: Beryllium copper Contact Surface Treatment: Tin Accommodated Contact Quantity: 2 Polarization Type: Off center hole Projection Length Above Mounting Surface:
Thread Direction: Right-hand Body Style: Top mount w/metal saddle and bushings Overall Length: 1.570 inches Overall Height: 0.716 inches Overall Width: 0.730 inches Mounting Hole Diameter: 0.138 inches Distance Between Mounting Facility Centers: Between 1.177 inches and 1.197 inches Mounting Hole Style: Two mounting holes/slots, in-line Contact Maximum Current Rating In Amps: 15.0 Contact Material: Beryllium copper Contact Surface Treatment: Tin Accommodated Contact Quantity: 2 Polarization Type: Off center hole Projection Length Above Mounting Surface:
Right-handBody Style:Top mount w/metal saddle and bushingsOverall Length:1.570 inchesOverall Height:0.716 inchesOverall Width:0.730 inchesMounting Hole Diameter:0.138 inchesDistance Between Mounting Facility Centers:Between 1.177 inches and 1.197 inchesMounting Hole Style:Two mounting holes/slots, in-lineContact Maximum Current Rating In Amps:15.0Contact Material:Beryllium copperContact Surface Treatment:TinAccommodated Contact Quantity:2Polarization Type:Off center holeProjection Length Above Mounting Surface:
Body Style:Top mount w/metal saddle and bushingsOverall Length:1.570 inchesOverall Height:0.716 inchesOverall Width:0.730 inchesMounting Hole Diameter:0.138 inchesDistance Between Mounting Facility Centers:Between 1.177 inches and 1.197 inchesMounting Hole Style:Two mounting holes/slots, in-lineContact Maximum Current Rating In Amps:15.0Contact Material:Beryllium copperContact Surface Treatment:TinAccommodated Contact Quantity:2Polarization Type:Off center holeProjection Length Above Mounting Surface:
Top mount w/metal saddle and bushings Overall Length: 1.570 inches Overall Height: 0.716 inches Overall Width: 0.730 inches Mounting Hole Diameter: 0.730 inches Mounting Hole Diameter: 0.138 inches Distance Between Mounting Facility Centers: Between 1.177 inches and 1.197 inches Mounting Hole Style: Two mounting holes/slots, in-line Contact Maximum Current Rating In Amps: 15.0 Contact Material: Beryllium copper Contact Surface Treatment: Tin Accommodated Contact Quantity: 2 Polarization Type: Off center hole Projection Length Above Mounting Surface:
Overall Length:1.570 inchesOverall Height:0.716 inchesOverall Width:0.730 inchesMounting Hole Diameter:0.138 inchesDistance Between Mounting Facility Centers:Between 1.177 inches and 1.197 inchesMounting Hole Style:Two mounting holes/slots, in-lineContact Maximum Current Rating In Amps:15.0Beryllium copperContact Surface Treatment:TinAccommodated Contact Quantity:2Polarization Type:Off center holeProjection Length Above Mounting Surface:
 1.570 inches Overall Height: 0.716 inches Overall Width: 0.730 inches Mounting Hole Diameter: 0.730 inches Mounting Hole Diameter: 0.138 inches Distance Between Mounting Facility Centers: Between 1.177 inches and 1.197 inches Mounting Hole Style: Two mounting holes/slots, in-line Contact Maximum Current Rating In Amps: 15.0 Contact Material: Beryllium copper Contact Surface Treatment: Tin Accommodated Contact Quantity: 2 Polarization Type: Off center hole Projection Length Above Mounting Surface:
Overall Height:0.716 inchesOverall Width:0.730 inchesMounting Hole Diameter:0.138 inchesDistance Between Mounting Facility Centers:Between 1.177 inches and 1.197 inchesMounting Hole Style:Two mounting holes/slots, in-lineContact Maximum Current Rating In Amps:15.0Contact Material:Beryllium copperContact Surface Treatment:TinAccommodated Contact Quantity:2Polarization Type:Off center holeProjection Length Above Mounting Surface:
0.716 inches Overall Width: 0.730 inches Mounting Hole Diameter: 0.138 inches Distance Between Mounting Facility Centers: Distance Between Mounting Facility Centers: Between 1.177 inches and 1.197 inches Mounting Hole Style: Two mounting holes/slots, in-line Contact Maximum Current Rating In Amps: 15.0 Contact Material: Beryllium copper Contact Surface Treatment: Tin Accommodated Contact Quantity: 2 Polarization Type: Off center hole Projection Length Above Mounting Surface:
Overall Width:0.730 inchesMounting Hole Diameter:0.138 inchesDistance Between Mounting Facility Centers:Between 1.177 inches and 1.197 inchesMounting Hole Style:Two mounting holes/slots, in-lineContact Maximum Current Rating In Amps:15.0Contact Material:Beryllium copperContact Surface Treatment:TinAccommodated Contact Quantity:2Polarization Type:Off center holeProjection Length Above Mounting Surface:
0.730 inches Mounting Hole Diameter: 0.138 inches Distance Between Mounting Facility Centers: Between 1.177 inches and 1.197 inches Mounting Hole Style: Two mounting holes/slots, in-line Contact Maximum Current Rating In Amps: 15.0 Contact Material: Beryllium copper Contact Surface Treatment: Tin Accommodated Contact Quantity: 2 Polarization Type: Off center hole Projection Length Above Mounting Surface:
Mounting Hole Diameter:0.138 inchesDistance Between Mounting Facility Centers:Between 1.177 inches and 1.197 inchesMounting Hole Style:Two mounting holes/slots, in-lineContact Maximum Current Rating In Amps:15.0Contact Material:Beryllium copperContact Surface Treatment:TinAccommodated Contact Quantity:2Polarization Type:Off center holeProjection Length Above Mounting Surface:
0.138 inches Distance Between Mounting Facility Centers: Between 1.177 inches and 1.197 inches Mounting Hole Style: Two mounting holes/slots, in-line Contact Maximum Current Rating In Amps: 15.0 Contact Material: Beryllium copper Contact Surface Treatment: Tin Accommodated Contact Quantity: 2 Polarization Type: Off center hole Projection Length Above Mounting Surface:
Distance Between Mounting Facility Centers:Between 1.177 inches and 1.197 inchesMounting Hole Style:Two mounting holes/slots, in-lineContact Maximum Current Rating In Amps:15.0Contact Material:Beryllium copperContact Surface Treatment:TinAccommodated Contact Quantity:2Polarization Type:Off center holeProjection Length Above Mounting Surface:
Between 1.177 inches and 1.197 inches Mounting Hole Style: Two mounting holes/slots, in-line Contact Maximum Current Rating In Amps: 15.0 Contact Material: Beryllium copper Contact Surface Treatment: Tin Accommodated Contact Quantity: 2 Polarization Type: Off center hole Projection Length Above Mounting Surface:
Mounting Hole Style:Two mounting holes/slots, in-lineContact Maximum Current Rating In Amps:15.0Contact Material:Beryllium copperContact Surface Treatment:TinAccommodated Contact Quantity:2Polarization Type:Off center holeProjection Length Above Mounting Surface:
Two mounting holes/slots, in-line Contact Maximum Current Rating In Amps: 15.0 Contact Material: Beryllium copper Contact Surface Treatment: Tin Accommodated Contact Quantity: 2 Polarization Type: Off center hole Projection Length Above Mounting Surface:
Contact Maximum Current Rating In Amps: 15.0 Contact Material: Beryllium copper Contact Surface Treatment: Tin Accommodated Contact Quantity: 2 Polarization Type: Off center hole Projection Length Above Mounting Surface:
 15.0 Contact Material: Beryllium copper Contact Surface Treatment: Tin Accommodated Contact Quantity: 2 Polarization Type: Off center hole Projection Length Above Mounting Surface:
Contact Material: Beryllium copper Contact Surface Treatment: Tin Accommodated Contact Quantity: 2 Polarization Type: Off center hole Projection Length Above Mounting Surface:
Beryllium copper Contact Surface Treatment: Tin Accommodated Contact Quantity: 2 Polarization Type: Off center hole Projection Length Above Mounting Surface:
Contact Surface Treatment: Tin Accommodated Contact Quantity: 2 Polarization Type: Off center hole Projection Length Above Mounting Surface:
Tin Accommodated Contact Quantity: 2 Polarization Type: Off center hole Projection Length Above Mounting Surface:
Accommodated Contact Quantity: 2 Polarization Type: Off center hole Projection Length Above Mounting Surface:
2 Polarization Type: Off center hole Projection Length Above Mounting Surface:
Polarization Type: Off center hole Projection Length Above Mounting Surface:
Off center hole Projection Length Above Mounting Surface:
Projection Length Above Mounting Surface:
Between 0.025 inches and 0.031 inches
Mounting Method:
Threaded hole
Mounting Type For Which Designed:
Mounting Type For Which Designed: Chassis
Chassis
Chassis Thready Qty Per Inch (tpi):
Chassis Thready Qty Per Inch (tpi): 32
Chassis Thready Qty Per Inch (tpi): 32 Thread Size:



Ground Terminal Type And Quantity:

1 tab, solder lug

Thread Series Designator:

Unc

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A02300