## NSN 5935-00-931-1942

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-931-1942 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape threaded **Overall Length:** 0.781 inches **Overall Diameter:** 1.125 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Connector Locking Method:** Snap ring Thread Length: 0.156 inches Thread Size: 0.875 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Solder well single mating end single contact grouping **Contact Material Specification:** Qq-b-330, comp a federal specification single material response single mating end single contact grouping **Insert Material Specification:** Mil-m-14, type sdg-f military specification single material response single mating end **Included Contact Quantity:** 6 single mating end single contact grouping **Bushing Accommodation Hole Shape:** 

Round

## NSN 5935-00-931-1942

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.006 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
Δ039h0

Mil-std (military Standard):

Mil-m-14 spec.