## NSN 5935-00-931-2424

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-931-2424
Body Style:
Straight shape, external coupling
Overall Length:
1.453 inches
Overall Diameter:
1.250 inches
Environmental Protection:
Moisture resistant and vibration resistant and salt water resistant
Mating End Quantity:
1
Contact Position Arrangement Style:
14-5 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1000.0 single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
0.0
Shell Type:
Potting
Connector Locking Method:
Bayonet pin
Connector Cable Strain Relief Method:
Potting type
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Og-n-416 type 2 of 3 federal energication single treatment response

Qq-p-416, type 2, cl 3 federal specification single treatment response

**Shell Material Specification:** 

Qq-a-591 federal specification single material response

**Included Contact Quantity:** 

5 single mating end single contact grouping

## **NSN 5935-00-931-2424**Electrical Plug Connector - Page 2 of 2

Fiig: A039b0



Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.025 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-c-26482 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No