

View Online at <https://aerobasegroup.com/nsn/5935-00-931-3004>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, internal coupling

**Overall Length:**

Between 0.477 inches and 0.510 inches

**Overall Diameter:**

0.125 inches

**Environmental Protection:**

Corrosion resistant and heat resistant and moisture resistant and shock proof and vibration proof

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

2

**Contact Position Arrangement Style:**

Sma all mating ends

**Contact Removability:**

Nonremovable all mating ends single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 all mating ends single contact grouping

**Thready Qty Per Inch (tpi):**

36

**Thread Size:**

0.250 inches

**Contact Material:**

Copper alloy all mating ends single contact grouping

**Contact Surface Treatment:**

Gold all mating ends single contact grouping

**Contact Surface Treatment Specification:**

Mil-g-45204 type 2, cl 2 military specification single treatment response all mating ends single contact grouping

**Contact Material Specification:**

Qq-c-530 federal specification single material response all mating ends single contact grouping

**Shell Material:**

Stainless steel

**Shell Surface Treatment:**

Passivate

**Shell Material Specification:**

Qq-s-764 type 303 federal specification single material response

**Included Contact Quantity:**

1 all mating ends single contact grouping

**Included Contact Type:**

Coaxial socket all mating ends single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.010 gold grains, troy

**Precious Material:**

Gold

**Thread Series Designator:**

Uns

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.