Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-931-3763

Thread Class:

2a and 2b

**Thread Direction:** 

Right-hand

#### **Body Style:**

Straight shape

# **Overall Length:**

1.250 inches

#### **Overall Height:**

1.032 inches

**Overall Width:** 

0.380 inches

#### **Environmental Protection:**

Shock resistant and vibration resistant

#### **Threaded Device Type:**

Coupling facility

#### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

34 single mating end

#### Contact Removability:

Nonremovable single mating end single contact grouping

# **Polarization Method:**

Jackscrew

#### **Connector Locking Method:**

Jackscrew-socket

#### Thready Qty Per Inch (tpi):

56

# Thread Size:

0.086 inches

#### **Terminal Location:**

Back single mating end single contact grouping

# **Contact Material:**

Copper alloy single mating end single contact grouping

# **Contact Surface Treatment:**

Gold single mating end single contact grouping

# Insert Material:

Plastic diallyl phthalate glass filled single mating end

# Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1 military specification single treatment response single mating end single contact grouping

# **Terminal Type:**

Solder well single mating end single contact grouping

# NSN 5935-00-931-3763

Electrical Plug Connector - Page 2 of 2



**Insert Material Specification:** Mil-p-19833, ty gdi-30f military specification single material response single mating end Included Contact Quantity: 34 single mating end single contact grouping Included Contact Type: Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.034 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.