## NSN 5935-00-931-4029

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-931-4029

view Online at https://aerobasegroup.com/nsn/5935-00-931-4029
Body Style:
Straight shape
Overall Length:
Between 2.714 inches and 2.744 inches
Overall Height:
0.683 inches
Overall Width:
Between 0.479 inches and 0.509 inches
Unthreaded Mounting Hole Diameter:
Between 0.115 inches and 0.125 inches
Distance Between Mounting Facility Centers:
Between 2.495 inches and 2.505 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
25w3 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Steel
Shell Surface Treatment:
Cadmium and chromate

**Insert Material Specification:** 

Mil-p-19833, type gdi-30f military specification single material response single mating end

**Included Contact Quantity:** 

22 single mating end single contact grouping

## NSN 5935-00-931-4029

Electrical Receptacle Connector - Page 2 of 2



Inc	luded	d Con	tact	Type:
	IUUC	4 <b>O</b> OH	ıavı	IVDC.

Round socket single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:** 

0.022 gold grains, troy and 0.022 silver grains, troy

**Precious Material:** 

Gold and silver

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-p-19833 spec.