

View Online at https://aerobasegroup.com/nsn/5935-00-931-4037

Body Material: Plastic Thread Class: 2a Thread Direction: Right-hand Body Style: Top mount w/studs Overall Length: 1.340 inches Overall Height: 0.340 inches Overall Width: 0.410 inches Body Mounting Hole Accommodation Length: 0.470 inches Body Mounting Hole Accommodation Length: 0.410 inches Body Mounting Hole Accommodation Vidth: 0.410 inches Distance Between Mounting Facility Centers: 1.062 inches Mounting Hole Style: Rectangular, w/two mounting holes/slots Contact Material: Copper alloy Contact Surface Treatment: Gold and silver Accommodated Contact Quantity: 8 Projection Length Below Mounting Surface: 0.375 inches Mounting Type For Which Designed: Chassis Thread Stud Mounting Type For Which Designed: Chassis Thread Size: <tr< th=""><th></th></tr<>	
Thread Class: 2a Thread Direction: Right-hand Body Style: Top mount w/studs Overall Length: 1.340 inches Overall Height: 0.840 inches Overall Width: 0.840 inches Overall Width: 0.840 inches Body Mounting Hole Accommodation Length: 0.750 inches Body Mounting Hole Accommodation Vidth: 0.760 inches Body Mounting Hole Accommodation Vidth: 0.760 inches Body Mounting Hole Accommodation Vidth: 0.410 inches Distance Between Mounting Facility Centers: 1.062 inches Mounting Hole Style: Rectangular, w/two mounting holes/slots Contact Material: Copper alloy Contact Surface Treatment: Gold and silver Accommodated Contact Quantity: 8 Projection Length Below Mounting Surface: 0.375 inches Mounting Method: Threadd stud Mounting Type For Which Designed: Chassis <td>Body Material:</td>	Body Material:
2a Thread Direction: Right-hand Body Style: Top mount w/studs Overall Length: 1.340 inches Overall Height: 0.840 inches Overall Width: 0.410 inches Body Mounting Hole Accommodation Length: 0.750 inches Body Mounting Hole Accommodation Width: 0.410 inches Distance Between Mounting Facility Centers: 1.062 inches Mounting Hole Style: Rectangular, w/two mounting holes/slots Contact Material: Copper alloy Contact Surface Treatment: Gold and silver Accommodated Contact Quantity: 8 Projection Length Below Mounting Surface: 0.375 inches Mounting Type For Which Designed: Chassis Threaded stud Mounting Type For Which Designed: Chassis Threaded Style: Au Chassis Thread Size: 0.112 inches Contact Position Arrangement Style:	
Thread Direction:Right-handBody Style:Top mount w/studsOverall Length:1.340 inchesOverall Height:0.840 inchesOverall Width:0.840 inchesOverall Width:0.410 inchesBody Mounting Hole Accommodation Length:0.750 inchesBody Mounting Hole Accommodation Width:0.410 inchesDistance Between Mounting Facility Centers:1.062 inchesMounting Hole Style:Rectangular, w/two mounting holes/slotsContact Material:Copper alloyContact Surface Treatment:Gold and silverAccommodated Contact Quantity:8Projection Length Below Mounting Surface:0.375 inchesMounting Method:Threaded studMounting Type For Which Designed:ChasisThready Qty Per Inch (tpi):40Thread Size:0.112 inchesContact Position Arrangement Style:	
Right-hand Body Style: Top mount w/studs Overall Length: 1.340 inches Overall Height: 0.840 inches Overall Width: 0.840 inches Overall Width: 0.410 inches Body Mounting Hole Accommodation Length: 0.750 inches Body Mounting Hole Accommodation Width: 0.410 inches Distance Between Mounting Facility Centers: 1.062 inches Mounting Hole Style: Rectangular, w/two mounting holes/slots Contact Material: Copper alloy Contact Surface Treatment: Gold and silver Accommodated Contact Quantity: 8 Projection Length Below Mounting Surface: 0.375 inches Mounting Method: Threaded stud Mounting Type For Which Designed: Chassis Thready Qty Per Inch (tpi): 40 Thread Size: 0.112 inches	
Body Style: Top mount w/studs Overall Length: 1.340 inches Overall Height: 0.840 inches Overall Width: 0.410 inches Body Mounting Hole Accommodation Length: 0.750 inches Body Mounting Hole Accommodation Width: 0.410 inches Body Inches Body Mounting Hole Accommodation Width: 0.410 inches Distance Between Mounting Facility Centers: 1.062 inches Mounting Hole Style: Rectangular, w/two mounting holes/slots Contact Material: Copper alloy Contact Surface Treatment: Gold and silver Accommodated Contact Quantity: 8 Projection Length Below Mounting Surface: 0.375 inches Mounting Method: Threaded stud Mounting Type For Which Designed: <td< td=""><td>Thread Direction:</td></td<>	Thread Direction:
Top mount w/studs Overall Length: 1.340 inches Overall Height: 0.840 inches Overall Width: 0.840 inches Overall Width: 0.410 inches Body Mounting Hole Accommodation Length: 0.750 inches Body Mounting Hole Accommodation Width: 0.410 inches Distance Between Mounting Facility Centers: 1.062 inches Mounting Hole Style: Rectangular, w/two mounting holes/slots Contact Material: Copper alloy Contact Surface Treatment: Gold and silver Accommodated Contact Quantity: 8 Projection Length Below Mounting Surface: 0.375 inches Mounting Method: Threaded stud Mounting Type For Which Designed: Chassis Thready Qty Per Inch (tpi): 40 Thread Size: 0.112 inches	-
Overall Length:1.340 inchesOverall Height:0.840 inchesOverall Width:0.410 inchesBody Mounting Hole Accommodation Length:0.750 inchesBody Mounting Hole Accommodation Width:0.410 inchesDistance Between Mounting Facility Centers:1.062 inchesMounting Hole Style:Rectangular, w/two mounting holes/slotsContact Material:Copper alloyContact Surface Treatment:Gold and silverAccommodated Contact Quantity:8Projection Length Below Mounting Surface:0.375 inchesMounting Type For Which Designel:ChassisThreaded studMounting Type For Which Designel:ChassisThread Size:0.112 inchesContact Narangement Style:	
1.340 inches Overall Height: 0.840 inches Overall Width: 0.410 inches Body Mounting Hole Accommodation Length: 0.750 inches Body Mounting Hole Accommodation Width: 0.410 inches Dotation Eletween Mounting Facility Centers: 1.062 inches Mounting Hole Style: Rectangular, w/two mounting holes/slots Contact Material: Copper alloy Contact Surface Treatment: Gold and silver 8 Projection Length Below Mounting Surface: 0.375 inches Mounting Method: Threaded stud Mounting Type For Which Designel: Chassis Thready Qty Per Inch (tpi): 40 Thread Size: 0.112 inches Contact Position Arrangement Style:	
Overall Height:0.840 inchesOverall Width:0.410 inchesBody Mounting Hole Accommodation Length:0.750 inchesBody Mounting Hole Accommodation Width:0.410 inchesDistance Between Mounting Facility Centers:1.062 inchesMounting Hole Style:Rectangular, w/two mounting holes/slotsContact Material:Copper alloyContact Surface Treatment:Gold and silverAccommodated Contact Quantity:8Projection Length Below Mounting Surface:0.375 inchesMounting Type For Which Designed:ChassisThreaded studMounting Type For Which Designed:ChassisThread Size:0.112 inchesContact Naterial:0.112 inches	-
0.840 inches Overall Width: 0.410 inches Body Mounting Hole Accommodation Length: 0.750 inches Body Mounting Hole Accommodation Width: 0.750 inches Body Mounting Hole Accommodation Width: 0.410 inches Distance Between Mounting Facility Centers: 1.062 inches Mounting Hole Style: Rectangular, w/two mounting holes/slots Contact Material: Copper alloy Contact Material: Copper alloy Contact Surface Treatment: Gold and silver Accommodated Contact Quantity: 8 Projection Length Below Mounting Surface: 0.375 inches Mounting Method: Threaded stud Mounting Type For Which Designed: Chassis Thready Qty Per Inch (tpi): 40 Thread Size: 0.112 inches	1.340 inches
Overall Width:0.410 inchesBody Mounting Hole Accommodation Length:0.750 inchesBody Mounting Hole Accommodation Width:0.410 inchesDistance Between Mounting Facility Centers:1.062 inchesMounting Hole Style:Rectangular, w/two mounting holes/slotsContact Material:Copper alloyContact Surface Treatment:Gold and silverAccommodated Contact Quantity:8Projection Length Below Mounting Surface:0.375 inchesMounting Type For Which Designed:ChassisThready Qty Per Inch (tpi):40Thread Size:0.112 inchesContact Position Arrangement Style:	Overall Height:
0.410 inches Body Mounting Hole Accommodation Length: 0.750 inches Body Mounting Hole Accommodation Width: 0.410 inches Distance Between Mounting Facility Centers: 1.062 inches Mounting Hole Style: Rectangular, w/two mounting holes/slots Contact Material: Copper alloy Contact Surface Treatment: Gold and silver Accommodated Contact Quantity: 8 Projection Length Below Mounting Surface: 0.375 inches Mounting Method: Threaded stud Mounting Type For Which Designed: Chassis Thready Qty Per Inch (tpi): 40 Thread Size: 0.112 inches	0.840 inches
Body Mounting Hole Accommodation Length:0.750 inchesBody Mounting Hole Accommodation Width:0.410 inchesDistance Between Mounting Facility Centers:1.062 inchesMounting Hole Style:Rectangular, w/two mounting holes/slotsContact Material:Copper alloyContact Surface Treatment:Gold and silverAccommodated Contact Quantity:8Projection Length Below Mounting Surface:0.375 inchesMounting Type For Which Designed:ChassisThreadd stud40Thread Size:0.112 inchesContact Position Arrangement Style:	Overall Width:
0.750 inches Body Mounting Hole Accommodation Width: 0.410 inches Distance Between Mounting Facility Centers: 1.062 inches Mounting Hole Style: Rectangular, w/two mounting holes/slots Contact Material: Copper alloy Contact Surface Treatment: Gold and silver Accommodated Contact Quantity: 8 Projection Length Below Mounting Surface: 0.375 inches Mounting Method: Threaded stud Mounting Type For Which Designed: Chassis Thready Qty Per Inch (tpi): 40 Thread Size: 0.112 inches	0.410 inches
Body Mounting Hole Accommodation Width: 0.410 inches Distance Between Mounting Facility Centers: 1.062 inches Mounting Hole Style: Rectangular, w/two mounting holes/slots Contact Material: Copper alloy Contact Surface Treatment: Gold and silver Accommodated Contact Quantity: 8 Projection Length Below Mounting Surface: 0.375 inches Mounting Method: Threaded stud Mounting Type For Which Designed: Chassis Thready Qty Per Inch (tpi): 40 Thread Size: 0.112 inches	Body Mounting Hole Accommodation Length:
0.410 inches Distance Between Mounting Facility Centers: 1.062 inches Mounting Hole Style: Rectangular, w/two mounting holes/slots Contact Material: Copper alloy Contact Surface Treatment: Gold and silver Accommodated Contact Quantity: 8 Projection Length Below Mounting Surface: 0.375 inches Mounting Method: Threaded stud Mounting Type For Which Designed: Chassis Thready Qty Per Inch (tpi): 40 Thread Size: 0.112 inches	0.750 inches
Distance Between Mounting Facility Centers: 1.062 inches Mounting Hole Style: Rectangular, w/two mounting holes/slots Contact Material: Copper alloy Contact Surface Treatment: Gold and silver Accommodated Contact Quantity: 8 Projection Length Below Mounting Surface: 0.375 inches Mounting Method: Threaded stud Mounting Type For Which Designed: Chassis Thready Qty Per Inch (tpi): 40 Thread Size: 0.112 inches	Body Mounting Hole Accommodation Width:
1.062 inches Mounting Hole Style: Rectangular, w/two mounting holes/slots Contact Material: Copper alloy Contact Surface Treatment: Gold and silver Accommodated Contact Quantity: 8 Projection Length Below Mounting Surface: 0.375 inches Mounting Method: Threaded stud Mounting Type For Which Designed: Chassis Thready Qty Per Inch (tpi): 40 Thread Size: 0.112 inches	0.410 inches
Mounting Hole Style:Rectangular, w/two mounting holes/slotsContact Material:Copper alloyContact Surface Treatment:Gold and silverAccommodated Contact Quantity:8Projection Length Below Mounting Surface:0.375 inchesMounting Method:Threaded studChassisThready Qty Per Inch (tpi):40Thread Size:0.112 inchesContact Position Arrangement Style:	Distance Between Mounting Facility Centers:
Rectangular, w/two mounting holes/slotsContact Material:Copper alloyContact Surface Treatment:Gold and silverAccommodated Contact Quantity:8Projection Length Below Mounting Surface:0.375 inchesMounting Method:Threaded studMounting Type For Which Designed:ChassisThready Qty Per Inch (tpi):40Thread Size:0.112 inchesContact Position Arrangement Style:	1.062 inches
Contact Material:Copper alloyContact Surface Treatment:Gold and silverAccommodated Contact Quantity:Accommodated Contact Quantity:8Projection Length Below Mounting Surface:0.375 inchesMounting Method:Threaded studMounting Type For Which Designed:ChassisThready Qty Per Inch (tpi):40Thread Size:0.112 inchesContact Position Arrangement Style:	Mounting Hole Style:
Copper alloy Contact Surface Treatment: Gold and silver Accommodated Contact Quantity: 8 Projection Length Below Mounting Surface: 0.375 inches Mounting Method: Threaded stud Mounting Type For Which Designed: Chassis Thready Qty Per Inch (tpi): 40 Thread Size: 0.112 inches Contact Position Arrangement Style:	Rectangular, w/two mounting holes/slots
Contact Surface Treatment: Gold and silver Accommodated Contact Quantity: 8 Projection Length Below Mounting Surface: 0.375 inches Mounting Method: Threaded stud Mounting Type For Which Designed: Chassis Thready Qty Per Inch (tpi): 40 Thread Size: 0.112 inches Contact Position Arrangement Style:	Contact Material:
Gold and silverAccommodated Contact Quantity:8Projection Length Below Mounting Surface:0.375 inchesMounting Method:Threaded studMounting Type For Which Designed:ChassisThready Qty Per Inch (tpi):40Thread Size:0.112 inchesContact Position Arrangement Style:	Copper alloy
Accommodated Contact Quantity: 8 Projection Length Below Mounting Surface: 0.375 inches Mounting Method: Threaded stud Mounting Type For Which Designed: Chassis Thready Qty Per Inch (tpi): 40 Thread Size: 0.112 inches Contact Position Arrangement Style:	Contact Surface Treatment:
8 Projection Length Below Mounting Surface: 0.375 inches Mounting Method: Threaded stud Mounting Type For Which Designed: Chassis Thready Qty Per Inch (tpi): 40 Thread Size: 0.112 inches Contact Position Arrangement Style:	Gold and silver
Projection Length Below Mounting Surface:0.375 inchesMounting Method:Threaded studMounting Type For Which Designed:ChassisThready Qty Per Inch (tpi):40Thread Size:0.112 inchesContact Position Arrangement Style:	Accommodated Contact Quantity:
0.375 inches Mounting Method: Threaded stud Mounting Type For Which Designed: Chassis Thready Qty Per Inch (tpi): 40 Thread Size: 0.112 inches Contact Position Arrangement Style:	8
Mounting Method: Threaded stud Mounting Type For Which Designed: Chassis Thready Qty Per Inch (tpi): 40 Thread Size: 0.112 inches Contact Position Arrangement Style:	Projection Length Below Mounting Surface:
Threaded stud Mounting Type For Which Designed: Chassis Thready Qty Per Inch (tpi): 40 Thread Size: 0.112 inches Contact Position Arrangement Style:	0.375 inches
Mounting Type For Which Designed: Chassis Thready Qty Per Inch (tpi): 40 Thread Size: 0.112 inches Contact Position Arrangement Style:	Mounting Method:
Chassis Thready Qty Per Inch (tpi): 40 Thread Size: 0.112 inches Contact Position Arrangement Style:	Threaded stud
Thready Qty Per Inch (tpi): 40 Thread Size: 0.112 inches Contact Position Arrangement Style:	Mounting Type For Which Designed:
40 Thread Size: 0.112 inches Contact Position Arrangement Style:	Chassis
Thread Size: 0.112 inches Contact Position Arrangement Style:	Thready Qty Per Inch (tpi):
0.112 inches Contact Position Arrangement Style:	40
Contact Position Arrangement Style:	Thread Size:
	0.112 inches
Dual in line	Contact Position Arrangement Style:
	Dual in line
Precious Material And Location:	Precious Material And Location:

Contact surfaces gold and contact surfaces silver



Precious Material And Weight:

0.008 gold grains, troy and 0.008 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unc

Terminal Type And Quantity:

8 solder well

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A02300