

View Online at <https://aerobasegroup.com/nsn/5935-00-932-2720>

**Body Style:**

Straight shape

**Overall Length:**

Between 2.155 inches and 2.165 inches

**Overall Width:**

0.330 inches

**Environmental Protection:**

Moisture proof and pressure proof

**Unthreaded Mounting Hole Diameter:**

Between 0.140 inches and 0.144 inches

**Distance Between Mounting Facility Centers:**

Between 1.802 inches and 1.812 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

29 single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

3.5 single mating end single contact grouping

**Polarization Method:**

Mating end

**Terminal Location:**

Back single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping

**Included Contact Quantity:**

29 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:**

0.029 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.