## NSN 5935-00-932-2720

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-932-2720

**Body Style:** 

Straight shape

**Overall Length:** 

Between 2.155 inches and 2.165 inches

**Overall Width:** 

0.330 inches

**Environmental Protection:** 

Moisture proof and pressure proof

**Unthreaded Mounting Hole Diameter:** 

Between 0.140 inches and 0.144 inches

**Distance Between Mounting Facility Centers:** 

Between 1.802 inches and 1.812 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

29 single mating end

**Contact Removability:** 

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

3.5 single mating end single contact grouping

**Polarization Method:** 

Mating end

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Insert Material:** 

Plastic single mating end

**Contact Surface Treatment Specification:** 

Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping

**Included Contact Quantity:** 

29 single mating end single contact grouping

**Included Contact Type:** 

Round pin single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:** 

0.029 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

## NSN 5935-00-932-2720

Electrical Receptacle Connector - Page 2 of 2



Unit Of Measure:	U	In	it	Of	Measure:
------------------	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.