NSN 5935-00-932-2720

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-932-2720

Body Style:

Straight shape

Overall Length:

Between 2.155 inches and 2.165 inches

Overall Width:

0.330 inches

Environmental Protection:

Moisture proof and pressure proof

Unthreaded Mounting Hole Diameter:

Between 0.140 inches and 0.144 inches

Distance Between Mounting Facility Centers:

Between 1.802 inches and 1.812 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

29 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

3.5 single mating end single contact grouping

Polarization Method:

Mating end

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping

Included Contact Quantity:

29 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.029 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

NSN 5935-00-932-2720

Electrical Receptacle Connector - Page 2 of 2



Unit Of Measure:	U	In	it	Of	Measure:
------------------	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.