NSN 5935-00-932-2769

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-932-2769 **Body Style:** Straight shape, external coupling **Overall Length:** 0.766 inches **Overall Height:** 1.141 inches **Overall Width:** 1.141 inches **Environmental Protection:** Vibration resistant and corrosion resistant **Unthreaded Mounting Hole Diameter:** 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.906 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.906 inches **Distance From Mounting Shoulder To Front Face:** 0.431 inches **Mating End Quantity: Contact Position Arrangement Style:** 14-44 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: **Connector Locking Method:** Bayonet pin **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic single mating end

NSN 5935-00-932-2769

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment Specification: Mil -g-45204 military specification single treatment response single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium **Included Contact Quantity:** 44 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.044 gold grains, troy **Precious Material:** Gold

Shelf Life:

Unit Of Measure:

Demilitarization:

Mil-std (military Standard):

N/a

No Fiig: A039b0

spec.