NSN 5935-00-932-4554

Contact Surface Treatment Specification:

Thread Class: 2a and 2b and 2a

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-932-4554

Thread Direction:
Right-hand and right-hand
Body Style:
Straight shape
Overall Length:
1.562 inches
Overall Height:
0.859 inches
Overall Width:
0.438 inches
Distance Between Mounting Facility Centers:
1.250 inches
Threaded Device Type:
Coupling facility and mounting stud
Mating End Quantity:
1
Contact Position Arrangement Style:
20 20-20 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
13.0 single mating end single contact grouping
Polarization Method:
Jackscrew
Connector Locking Method:
Jackscrew-socket
Thready Qty Per Inch (tpi):
32 and 32 and 32
Thread Size:
0.164 inches and 0.164 inches and 0.138 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic melamine mineral filled single mating end

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping

NSN 5935-00-932-4554

Mil-std (military Standard):

Mil-g-45204 spec.

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Solder well single mating end single contact grouping
Unable To Decode:
Unable to decode and unable to decode
Included Contact Quantity:
20 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Special Features:
Jackscrew type-male and location-left handandjackscrew type-female and location-right hand
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.020 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc and unc and unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
Δ030h0