

View Online at <https://aerobasegroup.com/nsn/5935-00-932-5241>

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, external coupling w/backshell

Overall Length:

Between 2.250 inches and 2.343 inches

Overall Diameter:

2.031 inches

Environmental Protection:

Watertight

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

28-16 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

22.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

Polarization Method:

Key, multiple key groove

Insert Position In Deg:

110.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thready Qty Per Inch (tpi):

28 and 18

Thread Size:

1.594 inches and 1.750 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate mineral filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 1, cl 2 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Anodize

Included Contact Quantity:

20 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.020 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Uns and uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.