NSN 5935-00-933-4617

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-933-4617 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.240 inches **Overall Diameter:** 0.630 inches **Environmental Protection:** Moisture resistant and vibration resistant **Cable Entrance Diameter:** 0.216 inches **Distance From Mounting Shoulder To Front Face:** 0.810 inches **Mounting Facility Thickness:** 0.241 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Bnc single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Bayonet latch **Connector Cable Strain Relief Method:** Compression nut Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping Thready Qty Per Inch (tpi): 28 **Thread Size:** 0.500 inches

Terminal Location:

Back single mating end single contact grouping

NSN 5935-00-933-4617

No Fiig: A039b0

Electrical Receptacle Connector - Page 2 of 2



| Contact Material: |
|--|
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Silver single mating end single contact grouping |
| Contact Surface Treatment Specification: |
| Qq-s-365 federal specification single treatment response single mating end single contact grouping |
| Terminal Type: |
| Solder well single mating end single contact grouping |
| Contact Material Specification: |
| Qq-c-530 federal specification single material response single mating end single contact grouping |
| Shell Material: |
| Copper alloy |
| Shell Material Specification: |
| Qq-b-626, alloy 360, 1/2 hard federal specification single material response |
| Included Contact Quantity: |
| 1 single mating end single contact grouping |
| Bushing Accommodation Hole Shape: |
| Round w/flat |
| Included Contact Type: |
| Coaxial socket single mating end single contact grouping |
| Precious Material And Location: |
| Contact surface silver |
| Precious Material And Weight: |
| 0.005 silver grains, troy |
| Precious Material: |
| Silver |
| Thread Series Designator: |
| Unef |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |