NSN 5935-00-934-1631

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-934-1631 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape w/cover **Unable To Decode:** Unable to decode and unable to decode **Overall Length:** 1.620 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 1.250 inches **Overall Width:** 1.620 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof **Unthreaded Mounting Hole Diameter:** 0.120 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.250 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** "3, 5-15" single mating end **Contact Removability:** Removable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 15.0 single mating end all contact groupings **Contact Maximum Ac Voltage Rating In Volts:** 120.0 single mating end all contact groupings **Polarization Method:** Contact Shell Type: Solid Thready Qty Per Inch (tpi): 18 **Thread Size:** 1.375 inches

Terminal Location:

Back single mating end all contact groupings

NSN 5935-00-934-1631

Electrical Receptacle Connector - Page 2 of 2



Contact Material:
Copper alloy single mating end all contact groupings
Terminal Type:
Screw single mating end all contact groupings
Shell Material:
Aluminum alloy
Included Contact Quantity:
2 single mating end 2nd contact grouping
Included Contact Type:
Flat socket single mating end 2nd contact grouping
Special Features:
Furnished items - chain and protective cover
Test Data Document:
81349-mil-c-3767 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef
Specification Data:
96906-ms25199 government standard
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-c-3767 spec.