

View Online at <https://aerobasegroup.com/nsn/5935-00-934-1631>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape w/cover

Unable To Decode:

Unable to decode and unable to decode

Overall Length:

1.620 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.250 inches

Overall Width:

1.620 inches

Environmental Protection:

Moisture proof and salt water resistant and vibration proof

Unthreaded Mounting Hole Diameter:

0.120 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.250 inches

Threaded Device Type:

Back shell

Mating End Quantity:

1

Contact Position Arrangement Style:

"3, 5-15" single mating end

Contact Removability:

Removable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

15.0 single mating end all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

120.0 single mating end all contact groupings

Polarization Method:

Contact

Shell Type:

Solid

Thready Qty Per Inch (tpi):

18

Thread Size:

1.375 inches

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Terminal Type:

Screw single mating end all contact groupings

Shell Material:

Aluminum alloy

Included Contact Quantity:

2 single mating end 2nd contact grouping

Included Contact Type:

Flat socket single mating end 2nd contact grouping

Special Features:

Furnished items - chain and protective cover

Test Data Document:

81349-mil-c-3767 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Specification Data:

96906-ms25199 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-c-3767 spec.