NSN 5935-00-934-2553

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-934-2553 **Thread Class:** 2a **Thread Direction:** Right-hand **Overall Length:** 0.448 inches **Bushing Diameter:** 0.244 inches **Overall Height:** 0.375 inches **Overall Width:** 0.375 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid **Connector Locking Method:** Externally threaded shell Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 single mating end single contact grouping **Thread Size:** 0.312 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Insert Material:** Plastic polytetrafluoroethylene single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Copper alloy **Shell Material Specification:**

Qq-b-626, 1/2 hard federal specification single material response

Included Contact Quantity:

1 single mating end single contact grouping

NSN 5935-00-934-2553

Electrical Receptacle Connector - Page 2 of 2



| Included Contact Type: |
|---|
| Coaxial pin single mating end single contact grouping |
| Special Features: |
| Printed circuit mtd |
| Thread Series Designator: |
| Unef |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A039b0