NSN 5935-00-934-2781

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-934-2781 **Body Style:** Straight shape w/solder mount **Overall Length:** 0.597 inches **Overall Diameter:** 0.854 inches **Environmental Protection:** Hermetic **Mating End Quantity: Contact Position Arrangement Style:** 10-dec single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic silicone mineral filled single mating end **Contact Surface Treatment Specification:** Mil-g-45204, type 2, class 2 military specification single treatment response single mating end single contact grouping **Terminal Type:** Turret single mating end single contact grouping **Shell Material:**

Aluminum alloy

Shell Surface Treatment:

Cadmium

Included Contact Quantity:

10 single mating end single contact grouping

NSN 5935-00-934-2781

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.010 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.