## NSN 5935-00-934-2845

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-934-2845 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Angle shape, internal coupling **Overall Length:** Between 1.719 inches and 1.843 inches **Overall Height:** 1.031 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 8-dec single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Key, multiple key groove **Insert Position In Deg:** 0.0 Shell Type: Potting **Connector Locking Method:** Internally threaded coupling ring **Connector Cable Strain Relief Method:** Potting type **Thread Length:** 0.844 inches Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.688 inches **Terminal Location:** Back single mating end single contact grouping

## NSN 5935-00-934-2845

Electrical Plug Connector - Page 2 of 2



(	Contact Material:
(	Copper alloy single mating end single contact grouping
C	Contact Surface Treatment:
(	Gold single mating end single contact grouping and silver single mating end single contact grouping
I	nsert Material:
F	Rubber single mating end
1	Ferminal Type:
5	Solder well single mating end single contact grouping
5	Shell Material:
F	Aluminum alloy
5	Shell Surface Treatment:
C	Cadmium and chromate
5	Shell Material Specification:
C	Qq-a-270 federal specification single material response
I	nsert Material Specification:
Ν	Mil-r-3065 military specification single material response single mating end
I	ncluded Contact Quantity:
8	3 single mating end single contact grouping
I	ncluded Contact Type:
F	Round pin single mating end single contact grouping
F	Precious Material And Location:
(	Contact surfaces gold and contact surfaces silver
F	Precious Material And Weight:
C	0.008 gold grains, troy and 0.008 silver grains, troy
F	Precious Material:
(	Gold and silver
1	Thread Series Designator:
ι	Jnef
5	Shelf Life:
١	N/a
ι	Jnit Of Measure:
-	-
0	Demilitarization:
١	No
F	Filg:

A039b0

Mil-std (military Standard):

Mil-r-3065 spec.