Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-934-3087

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling w/strain relief
Body Length:
5.832 inches
Overall Diameter:
2.463 inches
Cable Entrance Diameter:
Between 0.922 inches and 1.375 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
36-15 single mating end
Contact Removability:
Removable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
13.0 single mating end 2nd contact grouping
Contact Maximum Ac Voltage Rating In Volts:
900.0 single mating end 1st contact grouping
Contact Maximum Dc Voltage Rating In Volts:
700.0 single mating end 2nd contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
115.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
Connector Cable Strain Relief Method:
Cable clamp
Thready Qty Per Inch (tpi):
16
Thread Size:
2.250 inches
Terminal Location:
Back single mating end all contact groupings

## NSN 5935-00-934-3087

Electrical Plug Connector - Page 2 of 2



**Contact Material:** Copper alloy single mating end all contact groupings **Contact Surface Treatment:** Gold single mating end all contact groupings **Insert Material:** Rubber single mating end **Terminal Type:** Crimp single mating end all contact groupings Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium and chromate **Shell Surface Treatment Specification:** Qq-p-416, type 2, class 3 federal specification all treatment responses **Included Contact Quantity:** 34 single mating end 2nd contact grouping **Included Contact Type:** Round socket single mating end all contact groupings **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.035 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Un Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A039b0