

View Online at <https://aerobasegroup.com/nsn/5935-00-935-2129>

**Body Style:**

Straight shape, external coupling

**Overall Length:**

0.797 inches

**Overall Diameter:**

0.312 inches

**Environmental Protection:**

Moisture resistant and vibration resistant

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

C single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

1.5 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

400.0 single mating end single contact grouping

**Shell Type:**

Solid

**Connector Locking Method:**

Gear

**Connector Cable Strain Relief Method:**

Cable clamp

**Radio Frequency Type Contact Characteristic Impedance In Ohms:**

50.0 single mating end single contact grouping

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic tetrafluoroethylene single mating end

**Terminal Type:**

Solder well single mating end single contact grouping

**Shell Material:**

Copper alloy

**Shell Surface Treatment:**

Gold

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Coaxial pin single mating end single contact grouping

**Precious Material And Location:**

Contact surface and shell surface gold

**Precious Material And Weight:**

0.101 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0