

View Online at <https://aerobasegroup.com/nsn/5935-00-935-2230>

**Body Style:**

Straight shape w/o clamp

**Overall Height:**

2.625 inches

**Overall Diameter:**

0.500 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

Nonstd single mating end

**Contact Maximum Current Rating In Amps:**

10.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

125.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

125.0 single mating end single contact grouping

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, cl 1 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Female terminal connection single mating end single contact grouping

**Included Contact Quantity:**

1 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Color:**

Black and red

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.001 gold grains, troy

**Precious Material:**

Gold

**Test Data Document:**

81349-mil-p-2726 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-p-2726-30 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.