

View Online at https://aerobasegroup.com/nsn/5935-00-935-2231

Body Material:

Plastic

Body Style:

Bottom mount w/metal saddle

Fabrication Method:

Molded

Overall Length:

1.875 inches

Tempurature Rating:

100.0 degrees celsius

Overall Height:

1.016 inches

Overall Width:

1.375 inches

Mounting Hole Diameter:

Between 0.153 inches and 0.159 inches

Body Mounting Hole Accommodation Diameter:

1.109 inches

Distance Between Mounting Facility Centers:

Between 1.495 inches and 1.505 inches

Mounting Hole Style:

Round, w/two mounting holes

Contact Resistance In Ohms:

0.015

Specific Equipment Accommodated:

Electron tube

Contact Maximum Current Rating In Amps:

5.0

Contact Material:

Beryllium copper

Contact Surface Treatment:

Gold and copper

Accommodated Contact Quantity:

8

Polarization Type:

Center key hole

Saddle Material:

Brass

Saddle Surface Treatment:

Tin

Projection Length Above Mounting Surface:

Between 0.172 inches and 0.204 inches



Mounting Method:

Saddle

Mounting Type For Which Designed:

Chassis

Contact Position Arrangement Style:

Octal .687 inch

Ground Terminal Type And Quantity:

4 tab, solder lug

Contact Maximum Voltage In Volts And Current Type:

1250.0 ac and 1250.0 dc

Precious Material And Location:

COntact surfaces gold

Precious Material And Weight:

0.008 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-s-12883 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

8 tab, solder lug

Specification Data:

81349-mil-s-12883/1 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A02300