## NSN 5935-00-936-1764

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-936-1764 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 1.250 inches **Overall Height:** 0.574 inches **Overall Width:** 0.270 inches **Distance Between Mounting Facility Centers:** 1.000 inches **Threaded Device Type:** Mounting stud **Mating End Quantity:** 1 **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Guide pin/socket Thread Length: 0.190 inches Thready Qty Per Inch (tpi): 56 Thread Size: 0.086 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** 

Copper alloy single mating end single contact grouping

#### **Contact Surface Treatment:**

Gold single mating end single contact grouping and silver single mating end single contact grouping

#### **Insert Material:**

Plastic diallyl phthalate single mating end

#### **Terminal Type:**

Solder well single mating end single contact grouping

#### **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping

# NSN 5935-00-936-1764

Electrical Receptacle Connector - Page 2 of 2



#### **Insert Material Specification:**

Mil-m-14, type sdg-f military specification single material response single mating end

#### **Included Contact Quantity:**

6 single mating end single contact grouping

#### **Included Contact Type:**

Round socket single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold and contact surfaces silver

#### **Precious Material And Weight:**

0.006 gold grains, troy and 0.006 silver grains, troy

#### **Precious Material:**

Gold and silver

#### **Thread Series Designator:**

Unc

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0

### Mil-std (military Standard):

Mil-m-14 spec.