Electrical Plug Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-00-936-3787



Thread Class: 2b **Thread Direction: Right-hand Body Style:** Straight shape, internal coupling **Overall Length:** 2.188 inches **Overall Diameter:** 1.469 inches **Threaded Device Type:** Coupling facility Mating End Quantity: 1 **Contact Position Arrangement Style:** 20-24 single mating end **Contact Removability:** Nonremovable single mating end all contact groupings **Contact Maximum Current Rating In Amps:** 41.0 single mating end 2nd contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end all contact groupings **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end all contact groupings **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Potting **Connector Locking Method:** Internally threaded coupling nut **Connector Cable Strain Relief Method:** Potting type Thready Qty Per Inch (tpi): 18 Thread Size: 1.250 inches **Terminal Location:** Back single mating end all contact groupings **Contact Material:**

Copper alloy single mating end all contact groupings

NSN 5935-00-936-3787

Electrical Plug Connector - Page 2 of 2



Contact Surface Treatment:

Gold single mating end all contact groupings and silver single mating end all contact groupings or silver single mating end all contact groupings

Insert Material:

Plastic diallyl phthalate mineral filled single mating end

Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end all contact groupings and qq-s-365 federal specification 2nd treatment response single mating end all contact groupings or qq-s-365 federal specification 3rd treatment response single mating end all contact groupings

Terminal Type:

Solder well single mating end all contact groupings

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416, type ii, class 3 federal specification all treatment responses

Insert Material Specification:

Mil-m-14, type mdg military specification single material response single mating end

Included Contact Quantity:

2 single mating end 2nd contact grouping

Included Contact Type:

Round socket single mating end all contact groupings

Precious Material And Location:

Contact surfaces gold and contact surfaces silver or contact surfaces silver

Precious Material And Weight:

0.012 gold grains, troy and 0.012 silver grains, troy or 0.012 silver grains, troy

Precious Material:

Gold and silver or silver

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.