

View Online at <https://aerobasegroup.com/nsn/5935-00-937-2656>

**Body Style:**

Straight edge type w/mounting flange

**Overall Length:**

3.812 inches

**Overall Height:**

0.840 inches

**Overall Width:**

0.500 inches

**Unthreaded Mounting Hole Diameter:**

0.128 inches

**Distance Between Mounting Facility Centers:**

3.562 inches

**Board Accommodated Length:**

3.128 inches single board

**Board Accommodated Width:**

Between 0.054 inches and 0.072 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of independent contacts inserted board single mating end

**Contact Removability:**

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

3.0 single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:**

290.0 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

380.0 single mating end single contact grouping

**Connector Locking Method:**

Friction

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic polycarbonate single mating end

**Terminal Type:**

Crimp single mating end single contact grouping

**Insert Material Specification:**

L-p-393 federal specification single material response single mating end

**Included Contact Quantity:**

38 single mating end single contact grouping

**Included Contact Type:**

Bifurcated spring single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.038 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0