NSN 5935-00-937-9447



Thread Class: 2a **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 1.062 inches **Overall Height:** 0.578 inches **Overall Width:** 0.281 inches **Distance Between Mounting Facility Centers:** 0.814 inches **Threaded Device Type:** Mounting stud **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 20 20-20 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Guide pin/socket Thread Length: 0.220 inches Thready Qty Per Inch (tpi): 56 **Thread Size:** 0.086 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:**

Plastic diallyl phthalate single mating end

Solder well single mating end single contact grouping

Terminal Type:

Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-937-9447

NSN 5935-00-937-9447

Electrical Receptacle Connector - Page 2 of 2



Insert Material Specification:

Mil-m-14, sdg-f military specification single material response single mating end

Unable To Decode:

Unable to decode and unable to decode

Included Contact Quantity:

20 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.020 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.