## NSN 5935-00-938-4768

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-938-4768

**Body Style:** 

Straight edge type w/mounting flange

**Overall Length:** 

3.268 inches

**Overall Height:** 

Between 0.431 inches and 0.476 inches

**Overall Width:** 

Between 0.333 inches and 0.353 inches

**Environmental Protection:** 

Moisture resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:** 

0.128 inches

**Distance Between Mounting Facility Centers:** 

Between 2.930 inches and 3.046 inches

**Board Accommodated Length:** 

2.624 inches single board and 2.688 inches single board

**Board Accommodated Width:** 

Between 0.054 inches and 0.071 inches

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

2 rows of independent contacts inserted board single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:** 

5.0 single mating end single contact grouping

**Polarization Method:** 

Contact to contact polarizing keys

**Terminal Location:** 

Front single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Terminal Type:** 

Tab, solder lug single mating end single contact grouping

**Included Contact Quantity:** 

30 single mating end single contact grouping

**Included Contact Type:** 

Bifurcated spring single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold

## NSN 5935-00-938-4768

Electrical Receptacle Connector - Page 2 of 2



Precious	<b>Material And</b>	Weight:
lccicus	material Alla	Wongiit.

0.030 gold grains, troy

**Precious Material:** 

Gold

## **Test Data Document:**

81349-mil-c-21097 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-c-21097/1 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0