NSN 5935-00-939-6897

Body Style:

Overall Length: 4.125 inches Overall Height:

Hood, side opening, w/clamp

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-939-6897

1.953 inches
Overall Width:
1.250 inches
Environmental Protection:
Vibration resistant
Cable Entrance Diameter:
0.625 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
32 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
750.0 single mating end single contact grouping
Polarization Method:
Shell
Shell Type:
Hood, side opening
Connector Locking Method:
Latch
Connector Cable Strain Relief Method:
Cable clamp
Operating Tempurature Rating:
Between -55.0 degrees celsius and 125.0 degrees celsius
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 1, cl 2 military specification single treatment response single mating end single contact grouping

NSN 5935-00-939-6897

Mil-std (military Standard):

Mil-g-45204 spec.

Electrical Plug Connector - Page 2 of 2



Terminal Type:
Solder well single mating end single contact grouping
Contact Material Specification:
Qq-b-750, comp a federal specification single material response single mating end single contact grouping
Shell Material:
Copper alloy
Shell Surface Treatment:
Nickel
Shell Surface Treatment Specification:
Qq-n-281, class b federal specification single treatment response
Shell Material Specification:
Qq-b-613, comp 4 federal specification single material response
Insert Material Specification:
Mil-m-14, type mdg military specification single material response single mating end
Shell Guide Type And Location Designator:
A pin and e pin and 5 pin and 6 pin
Included Contact Quantity:
32 single mating end single contact grouping
Included Contact Type:
Leaf spring single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.036 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0