Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-939-6898

Overall Length
Overall Length:
3.970 inches
Overall Height:
1.000 inches
Overall Width:
Between 0.830 inches and 0.838 inches
Unthreaded Mounting Hole Diameter:
0.125 inches
Distance Between Mounting Facility Centers:
Between 3.622 inches and 3.628 inches
Mating End Quantity:
1
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Dc Voltage Rating In Volts:
750.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Shen Type.
Solid
Solid
Solid Connector Locking Method:
Solid Connector Locking Method: Lever-pin
Solid Connector Locking Method: Lever-pin Terminal Location:
Solid Connector Locking Method: Lever-pin Terminal Location: Back single mating end single contact grouping
Solid Connector Locking Method: Lever-pin Terminal Location: Back single mating end single contact grouping Contact Material:
Solid Connector Locking Method: Lever-pin Terminal Location: Back single mating end single contact grouping Contact Material: Copper single mating end single contact grouping
Solid Connector Locking Method: Lever-pin Terminal Location: Back single mating end single contact grouping Contact Material: Copper single mating end single contact grouping Contact Surface Treatment:
Solid Connector Locking Method: Lever-pin Terminal Location: Back single mating end single contact grouping Contact Material: Copper single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping
Solid Connector Locking Method: Lever-pin Terminal Location: Back single mating end single contact grouping Contact Material: Copper single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material:
Solid Connector Locking Method: Lever-pin Terminal Location: Back single mating end single contact grouping Contact Material: Copper single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end
Solid Connector Locking Method: Lever-pin Terminal Location: Back single mating end single contact grouping Contact Material: Copper single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end Terminal Type:
Solid Connector Locking Method: Lever-pin Terminal Location: Back single mating end single contact grouping Contact Material: Copper single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Tab, solder lug single mating end single contact grouping
Solid Connector Locking Method: Lever-pin Terminal Location: Back single mating end single contact grouping Contact Material: Copper single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Tab, solder lug single mating end single contact grouping Shell Material:
Solid Connector Locking Method: Lever-pin Terminal Location: Back single mating end single contact grouping Contact Material: Copper single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Tab, solder lug single mating end single contact grouping Shell Material: Copper alloy
Solid Connector Locking Method: Lever-pin Terminal Location: Back single mating end single contact grouping Contact Material: Copper single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Tab, solder lug single mating end single contact grouping Shell Material: Copper alloy
Solid Connector Locking Method: Lever-pin Terminal Location: Back single mating end single contact grouping Contact Material: Copper single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Insert Material: Plastic diallyl phthalate single mating end Terminal Type: Tab, solder lug single mating end single contact grouping Shell Material: Copper alloy Shell Surface Treatment:



Included Contact Type:

Leaf spring single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.032 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0