## NSN 5935-00-939-8123

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-939-8123

view Offiline at https://defobasegroup.com/histi/0000-00-000-00120
Body Style:
Straight shape, flush mount
Overall Length:
1.000 inches
Overall Height:
1.125 inches
Overall Width:
2.312 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.750 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
2.062 inches
Distance From Mounting Shoulder To Front Face:
0.750 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
32 single mating end
Contact Removability:
Nonremovable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
7.5 single mating end 2nd contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Friction
Operating Tempurature Rating:
Between -55.0 degrees celsius and 125.0 degrees celsius
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Insert Material:
Plastic single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy

## NSN 5935-00-939-8123

No Fiig: A039b0

Electrical Receptacle Connector - Page 2 of 2



## **Shell Surface Treatment:** Cadmium **Shell Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Included Contact Quantity:** 3 single mating end 1st contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material:** Gold and silver Shelf Life: N/a **Unit Of Measure:** Demilitarization: