## NSN 5935-00-940-3075

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-940-3075
Body Style:
Straight shape
Overall Length:
Between 2.714 inches and 2.744 inches
Overall Height:
0.668 inches
Overall Width:
Between 0.479 inches and 0.509 inches
Unthreaded Mounting Hole Diameter:
Between 0.086 inches and 0.091 inches
Distance Between Mounting Facility Centers:
Between 2.495 inches and 2.505 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
37 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Steel
Shell Surface Treatment:
Chromate and cadmium

**Insert Material Specification:** 

Mil-p-19833, ty gdi-30f military specification single material response single mating end

**Included Contact Quantity:** 

37 single mating end single contact grouping

## NSN 5935-00-940-3075

Electrical Receptacle Connector - Page 2 of 2



I	Incl	hul	ed	Co	ntac	:t ]	Γνη	۵.
ı		ıuu	cu	-	IILAV	<i>-</i> L	V	₹.

Round socket single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:** 

0.037 gold grains, troy and 0.037 silver grains, troy

**Precious Material:** 

Gold and silver

**Supplementary Features:** 

Mounting method - float

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-p-19833 spec.